



SHI-PRODUKTPASS

Produkte finden - Gebäude zertifizieren

SHI-Produktpass-Nr.:

14884-10-1017

tesa® INSULATION Türabdichtungen

Warengruppe: Zubehör & Werkzeuge



tesa SE
Hugo-Kirchberg-Straße 1
22848 Norderstedt



Produktqualitäten:



Köttner

Helmut Köttner
Wissenschaftlicher Leiter
Freiburg, den 18.08.2026



Inhalt

■ QNG - Qualitätssiegel Nachhaltiges Gebäude	1
■ DGNB Neubau 2023.2	2
■ DGNB Neubau 2023	3
■ DGNB Neubau 2018	4
Produktsiegel	5
Rechtliche Hinweise	6
Technisches Datenblatt/Anhänge	7

Wir sind stolz darauf, dass die SHI-Datenbank, die erste und einzige Datenbank für Bauprodukte ist, die ihre umfassenden Prozesse sowie die Aktualität regelmäßig von dem unabhängigen Prüfunternehmen SGS-TÜV Saar überprüfen lässt.





Produkt:

tesa® INSULATION Türabdichtungen

SHI Produktpass-Nr.:

14884-10-1017



QNG - Qualitätssiegel Nachhaltiges Gebäude

Das Qualitätssiegel Nachhaltiges Gebäude, entwickelt durch das Bundesministerium für Wohnen, Stadtentwicklung und Bauwesen (BMWSB), legt Anforderungen an die ökologische, soziokulturelle und ökonomische Qualität von Gebäuden fest. Das Sentinel Holding Institut prüft Bauprodukte gemäß den QNG-Anforderungen für eine Zertifizierung und vergibt das QNG-ready Siegel. Das Einhalten des QNG-Standards ist Voraussetzung für den KfW-Förderkredit. Für bestimmte Produktgruppen hat das QNG derzeit keine spezifischen Anforderungen definiert. Diese Produkte sind als nicht bewertungsrelevant eingestuft, können jedoch in QNG-Projekten genutzt werden.

Kriterium	Pos. / Bauproduktgruppe	Betrachtete Stoffe	QNG Freigabe
3.1.3 Schadstoffvermeidung in Baumaterialien			QNG-ready nicht bewertungsrelevant



Produkt:

tesa® INSULATION Türabdichtungen

SHI Produktpass-Nr.:

14884-10-1017



DGNB Neubau 2023.2

Kriterium	Pos. / Relevante Bauteile / Bau-Materialien / Flächen	Betrachtete Stoffe / Aspekte	Qualitätsstufe
ENV 1.2 Risiken für die lokale Umwelt			nicht bewertungsrelevant



Produkt:

tesa® INSULATION Türabdichtungen

SHI Produktpass-Nr.:

14884-10-1017



DGNB Neubau 2023

Das DGNB-System (Deutsche Gesellschaft für Nachhaltiges Bauen) bewertet die Nachhaltigkeit von Gebäuden verschiedener Art. Das System ist sowohl anwendbar für private und gewerbliche Großprojekte als auch für kleinere Wohngebäude. Die Version 2023 setzt hohe Standards für ökologische, ökonomische, soziokulturelle und funktionale Aspekte während des gesamten Lebenszyklus eines Gebäudes.

Kriterium	Pos. / Relevante Bauteile / Bau-Materialien / Flächen	Betrachtete Stoffe / Aspekte	Qualitätsstufe
ENV 1.2 Risiken für die lokale Umwelt, 03.05.2024 (3. Auflage)	nicht zutreffend		nicht bewertungsrelevant

Kriterium	Pos. / Relevante Bauteile / Bau-Materialien / Flächen	Betrachtete Stoffe / Aspekte	Qualitätsstufe
ENV 1.2 Risiken für die lokale Umwelt, 29.05.2025 (4. Auflage)	nicht zutreffend		nicht bewertungsrelevant



Produkt:

tesa® INSULATION Türabdichtungen

SHI Produktpass-Nr.:

14884-10-1017



DGNB Neubau 2018

Das DGNB-System (Deutsche Gesellschaft für Nachhaltiges Bauen) bewertet die Nachhaltigkeit von Gebäuden verschiedener Art. Das System ist sowohl anwendbar für private und gewerbliche Großprojekte als auch für kleinere Wohngebäude.

Kriterium	Pos. / Relevante Bauteile / Bau-Materialien / Flächen	Betrachtete Stoffe / Aspekte	Qualitätsstufe
ENV 1.2 Risiken für die lokale Umwelt	nicht zutreffend	nicht zutreffend	nicht bewertungsrelevant



Produkt:

tesa® INSULATION Türabdichtungen

SHI Produktpass-Nr.:

14884-10-1017



Produktsiegel

In der Baubranche spielt die Auswahl qualitativ hochwertiger Materialien eine zentrale Rolle für die Gesundheit in Gebäuden und deren Nachhaltigkeit. Produktlabels und Zertifikate bieten Orientierung, um diesen Anforderungen gerecht zu werden. Allerdings besitzt jedes Zertifikat und Label eigene Prüfkriterien, die genau betrachtet werden sollten, um sicherzustellen, dass sie den spezifischen Bedürfnissen eines Bauvorhabens entsprechen.



Produkte mit dem QNG-ready Siegel des Sentinel Holding Instituts eignen sich für Projekte, für welche das Qualitätssiegel Nachhaltiges Gebäude (QNG) angestrebt wird. QNG-ready Produkte erfüllen die Anforderungen des QNG Anhangdokument 3.1.3 "Schadstoffvermeidung in Baumaterialien". Das KfW-Kreditprogramm Klimafreundlicher Neubau mit QNG kann eine höhere Fördersumme ermöglichen.



Produkt:

tesa® INSULATION Türabdichtungen

SHI Produktpass-Nr.:

14884-10-1017



Rechtliche Hinweise

(*) Die Kriterien dieses Steckbriefs beziehen sich auf das gesamte Bauobjekt. Die Bewertung erfolgt auf der Ebene des Gebäudes. Im Rahmen einer sachgemäßen Planung und fachgerechten Installation können einzelne Produkte einen positiven Beitrag zum Gesamtergebnis der Bewertung leisten. Das Sentinel Holding Institut stützt sich einzig auf die Angaben des Herstellers.

Alle Kriterien finden Sie unter:

<https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfverfahren/kriterien%20f%C3%BCr%20Produkte>

Wir sind stolz darauf, dass die SHI-Datenbank, die erste und einzige Datenbank für Bauprodukte ist, die ihre umfassenden Prozesse sowie die Aktualität regelmäßig von dem unabhängigen Prüfunternehmen SGS-TÜV Saar überprüfen lässt.



Herausgeber

Sentinel Holding Institut GmbH
Bötzingen Str. 38
79111 Freiburg im Breisgau
Tel.: +49 761 590 481-70
info@sentinel-holding.eu
www.sentinel-holding.eu

tesa® Insulation Double#Sided Door Seal



Product Information

5418

Product Description

tesa® Insulation Double#Sided Door Seal protects against draughts, dust and noise. Quick, tool#free fitting with no drilling or glue. Ideal for under#door gaps up to 22 mm. Removes cleanly without residue.

Product Features

- Suitable for smooth, flat floors
- Perfect for under#door gaps up to 22 mm
- Stops draughts, dust, cold, heat, noise and insects
- Installs in seconds – no drilling or gluing
- Simply slide under the door leaf
- Double door bottom seal available in grey and white

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- Gap coverage up to 22 mm

Properties/Performance Values

- | | | | |
|------------------------|---|---------------------|---------------|
| • Chemical resistance | no | • Reusable | yes |
| • Material | Polyester, PE (polyethylene), LDPE (Low-density polyethylene) | • Solvent free | yes |
| | | • Suitable surfaces | Wooden floors |
| • Residue free removal | yes | | |

tesa® Insulation Double#Sided Door Seal

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=5418A>

tesa® Insulation Door Brush Seal for Carpets



Product Information

5403

Product Description

The tesa® INSULATION Door Brush Seal reliably protects against draughts, dust and noise. Perfect for carpets, it keeps warmth in and cold out to help save energy. Quick to fit, with no drilling or screws required.

Product Features

- Door bottom seal for carpeted floors
- Suitable for gaps up to 15 mm
- Self#adhesive: easy installation without screws or nails
- Material: plastic
- Durability: 6 years
- Variants: white, brown and transparent
- Also known as a draught excluder/door brush seal for carpets
- Helps reduce heat loss and block dust and noise

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------|----------------------|-------|
| • Type of adhesive | acrylic | • Gap coverage up to | 15 mm |
|--------------------|---------|----------------------|-------|

Properties/Performance Values

- | | | | |
|-----------------------|------------------|------------------------|---------|
| • Chemical resistance | no | • Residue free removal | no |
| • Durability | 6 years | • Solvent free | yes |
| • Material | PS (polystyrene) | • Suitable surfaces | Carpets |

tesa® Insulation Door Brush Seal for Carpets

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=5403A>

tesa® INSULATION Door Brush Seal for Uneven Floors



Product Information

5405

Product Description

tesa® INSULATION Door Brush Seal PREMIUM protects against draughts, dust, and noise. Ideal for uneven floors, it keeps warmth in and cold out. Easy to fit with no drilling or screws. Durable and long-lasting thanks to high-quality materials.

Product Features

- Painted aluminium door seal for gaps up to 15 mm
- Self-adhesive – no drilling or hammering needed
- Suitable for tiles, ceramics, and other uneven floors
- Active level adjustment via spring-loaded brush suspension (brush seal)
- Seals gap widths up to 15 mm
- Durability: up to 8 years
- Available finishes: white, brown, silver

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- Gap coverage up to 15 mm

Properties/Performance Values

- | | | | |
|-----------------------|---------------------|------------------------|------------------------|
| • Chemical resistance | no | • Residue free removal | no |
| • Durability | 8 years | • Solvent free | yes |
| • Material | Lacquered aluminium | • Suitable surfaces | Wooden floors, Carpets |

tesa® NSULATION Door Brush Seal for Uneven Floors

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=5405A>

tesa® INSULATION Door Brush Seal For Smooth And Slightly Uneven Floors



Product Information

5433

Product Description

The tesa® INSULATION Door Brush Seal protects against drafts, dust, and noise. Ideal for parquet, laminate, wooden plank, or PVC floors, it keeps warmth in and cold out. Easy application without drilling or screwing.

Product Features

- Draft excluder for smooth parquet, laminate, wooden or PVC floors
- Suitable for gaps up to 12 mm wide
- Self-adhesive: Easy installation without screws or nails
- Material: Plastic rail and nylon bristles
- Durability: 4 years
- Product variants: white, brown, and transparent

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- Gap coverage up to 12 mm

Properties/Performance Values

• Chemical Resistance	no	• Residue-free removability	no
• Durability	4 years	• Solvent free	yes
• Material	Plastic, PET (Polyethylene terephthalate), PP (polypropylene)	• Suitable surfaces	Wooden floors

tesa® INSULATION Door Brush Seal For Smooth And Slightly Uneven Floors

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=5433A>