

Krono Original wall and ceiling panels

LO 9005NF26

<u>dimensions</u>			
dimensions	thickness	10 mm	
	length	2600 mm	
	width	154 mm	
	length of the surface layer	2586 mm	
	width of surface layer with 0-groove	126,8 mm	
	width of surface layer with 1cm groove	134,2 mm	
profile	length: clic - nailed	width: snap	
joint variations	<input checked="" type="checkbox"/> 1 cm-groove <input type="checkbox"/> 0-groove	<input checked="" type="checkbox"/> shadow groove <input type="checkbox"/> 0-groove + embossed edge	
medium density fibre board	density	720 kg/m ³	
<u>tolerances</u>			
thickness of elements	DIN 68740-2	± 0,5 mm	
length of elements	DIN 68740-2	± 2 mm	
width of elements	DIN 68740-2	± 1 mm	
squareness	DIN 68740-2	2 mm/m = 0,2 %	
straightness	DIN 68740-2	1 mm/m = 0,1 %	
openings between elements	internal standard	≤ 0,3 mm	
height difference between elements	internal standard	≤ 0,4 mm	
<u>tests</u>			
splitting resistance	internal standard	≥ grade 4	
wipe resistance	internal standard	≥ grade 4	
thickness swelling	EN 317	≤ 20 %	
<u>environment</u>			
emission of formaldehyde		class E1	