


Rosen universal 48 Volt Lithium Speicher

Marke Wechselrichter	BMS Protokoll	Verbindung	getestete Modelle	Software	Battery model
PYLONTECH	CAN-Bus-protocol-PYLON	CAN	Applicable to all inverters using Pyener CAN protocol	V1.3	7.2kwh EJ/7.2kwh WD/9.6kwh EJ
固德威 GOODWE	Goodwe communication protocol	CAN	GW3648D-ES	V1.5	7.2kwh EJ/7.2kwh WD/9.6kwh EJ
solis	CAN communication protocol	CAN	RHI-5K-48ES	V1.0	7.2kwh EJ/7.2kwh WD/9.6kwh EJ
阳光电源 SUNGROW	CAN-Bus-protocol-PYLON	CAN	SH5K-30	V1.3	7.2kwh EJ/7.2kwh WD/9.6kwh EJ
SOFAR SOLAR 首航新能源	Description of CAN protocol for BMS general protocol of Sofar energy storage inverter	CAN	HYD 3000-ES	V1.0	7.2kwh EJ/7.2kwh WD/9.6kwh EJ
Growatt	Growatt BMS CAN-Bus-protocol-low-voltage	CAN	SPF 5000TL HVM-WPV-P SPF 10KT HVM;SPF series	V1.05	7.2kwh EJ/7.2kwh WD/9.6kwh EJ
Growatt	Growatt BMS communication protocol of growatt low voltage battery	CAN	Growatt SPH 5000	V1.01	7.2kwh EJ/7.2kwh WD/9.6kwh EJ
victron energy	can-bus_bms_protocol	CAN	MultiPLUS-II	V1.0	7.2kwh EJ/7.2kwh WD/9.6kwh EJ
LUXPOWERTEK	Luxpowertek Battery CAN Protocol	CAN	SNV5000-WPV SNA3000-5000	V1.0	7.2kwh EJ/7.2kwh WD/9.6kwh EJ
Sol-Ark LIMITLESS POWER	Sol-Ark CAN Bus Protocol	CAN	Sol-Ark 8K & 12K	V1.2	7.2kwh EJ/7.2kwh WD/9.6kwh EJ
STUDER	Technical specification Studer BMS Protocol	CAN	XTM 4000-48	V1.03	7.2kwh EJ/7.2kwh WD/9.6kwh EJ
tbb TBB POWER	TBB lithium battery BMS platform CAN communication protocol V1.02	CAN	RiiO Sun 5KVA-S CA3090L	V1.02	7.2kwh EJ/7.2kwh WD/9.6kwh EJ
Deye 德业	CAN-Bus-protocol-PYLON-v1.3	CAN	SUN-3 6KSG03LP1-EU	V1.0	7.2kwh EJ/7.2kwh WD/9.6kwh EJ
LIVOLTEK	LIVOLTEK CANBUS Protocol of Low Voltage SystemV1.0	CAN	GF1-3K48S1 GF1-5K48S1	V1.0	7.2kwh EJ/7.2kwh WD/9.6kwh EJ
SORO TEC Power Solutions Expert	2_CAN协议1.0	CAN	REVO III 5.5-8KVA	V1.0	7.2kwh EJ/7.2kwh WD/9.6kwh EJ
MEGAREVO	Megarevo Energy Technology Hybrid Inverter_5K_BMS Protocol V1.01	CAN	REVO_RKL1 R8KLNA	V1.01	7.2kwh EJ/7.2kwh WD/9.6kwh EJ
Afore	Luxpowertek Battery CAN Protocol	CAN	AF3K-SL AF5K-SL	V1.0	7.2kwh EJ/7.2kwh WD/9.6kwh EJ
Sacolar	Growatt BMS CAN-Bus-protocol-low-voltage	CAN	SP系列	V1.05	7.2kwh EJ/7.2kwh WD/9.6kwh EJ
PYLONTECH	RS485-protocol-pylon-low-voltage	485	Applicable Pineneng 485 protocol data summary report to the inverter inverter3K	V3.5	7.2kwh WD/9.6kwh EJ
srne	PACE BMS Modbus Protocol for RS485	485	HF4850S80-H;HF4850S80-145; HF2430S60-100	V1.3	7.2kwh WD/9.6kwh EJ
Growatt	SPF BMS RS485 protocol	485	SPF 5000TL HVM-WPV-P SPF 10KT HVM;SPF series	V2.01	7.2kwh WD/9.6kwh EJ
SMK SOLAR 斯曼科新能源	Lithium battery agreement GT version 20220510.html	485	Glory M5000 HHP-48L	V2.01	7.2kwh WD/9.6kwh EJ
Voltronic Power	Voltronic Inverter and BMS 485 communication protocol /FSP	485	InfiniSolar VII	V1.0	7.2kwh WD/9.6kwh EJ
EPEVER 汇能锂电	锂电池BMS-Link通讯地址表V1.4.pdf	485	UP5000-HM8042	V1.4	7.2kwh WD/9.6kwh EJ

Wir empfehlen immer, unabhängig von dieser Liste, die Kompatibilität individuell zu prüfen, da es manchmal zu Anpassungen aufgrund eines Softwareupdates kommt.
Schreiben Sie uns dazu ein Mail an: office@starke.at



Battery Specifications			
Model No	LFP48V100AH	LFP48V150AH	LFP48V200AH
Nominal Parameters			
Voltage	48 V	48 V	48 V
Capacity	100Ah	150Ah	200Ah
Energy	4.8 KWH	7.2 KWH	9.6 KWH
Dimensions (L x W x H)	680 x495 x190mm	680 x495 x190mm	680 x495 x190mm
Net Weight	67kg	80kg	96kg

