



Domestic users / Lights & Floodlights / Outdoor Lights / L 1

## L 1

### Information copy

Practical design. Practical sensor-switched outdoor light L 1, ideal for building entrances and building fronts, 180° angle of coverage, reach up to 10 m, selectable time and twilight threshold, includes sheet of house numbers.



### Details

**3 JAHRE**  
HERSTELLER  
GARANTIE  
steinel.de/garantie



2 - 2000 lux



IP44



ideal 2 m



max. 10 m



90° vertical



infrared sensor 180°



energy saving



8 sec - 35 min

# max.60w

max. 60 W E27



Including sheet of self-adhesive house numbers



Impact-resistant material rated to IK 07



UV-protected material

---

#### Technical specifications L 1 White

---

|                                               |                      |
|-----------------------------------------------|----------------------|
| European Article Number (EAN)                 | 4007841650513        |
| Dimensions(w x h x d):                        | 255 x 110 x 120 mm   |
| Voltage                                       | 230-240 V/50 Hz      |
| Sensor type                                   | Passive infrared     |
| Output                                        | 60 W max. / E 27     |
| Detection angle                               | 180°                 |
| Tilting range                                 | 90 °                 |
| Capability of masking out individual segments | Yes                  |
| Reach                                         | 10 m max.            |
| Time setting                                  | 8 sec. - 35 min.     |
| Response brightness                           | 2-2000 lx            |
| Degree of protection (IP)                     | IP44                 |
| Protection class                              | II                   |
| Impact strength                               | IK07                 |
| Material                                      | UV-resistant plastic |

---

**With lamp**

No

**Version**

White

**Sheet of self-adhesive house numbers**

included

**Application**

ideal for building entrances and fronts of buildings