

Confort

OCELAIR



Aires Acondicionado OCELAIR



- Smart Airflow
- Calentamiento y enfriamiento rápido
- Mantenimiento % humedad comfortable
- Super silencioso 22db
- Recordatorio limpieza filtro
- Drenaje dual
- Detección fugas refrigerante
- Wifi
- Eficiencia Energética A++ / A+

MODELOS			NMSP90A	NMSP120A	NMSP180A	NMSP240A
EAN			8436607753070	8436607753124	8436607753186	8436607753230
ALIMENTACION		V,F,HZ	220-240V (1 Fase - 50Hz)			
CAPACIDAD REFRIGERACION	CAPACIDAD	KW	2,6	3,4	5,1	6,8
		BTU/H	9000	12000	18000	24000
	CONSUMO	W	149	195	293	390
	SEER	-	6,1	6,1	6,1	6,1
	CLAS ENERGETICA	FRIO	A++	A++	A++	A++
CAPACIDAD CALEFACCION	CAPACIDAD	KW	2,20	2,4	5,00	5,8
		BTU/H	9000	12000	18000	24000
	CONSUMO	W	604	659	1373	1592
	SCOP	-	4,0	4,0	4,0	4,0
	CLAS ENERGETICA	Calor	A+	A+	A+	A+
UNIDAD INTERIOR	POTENCIA SONORA(S/H/M/L/Mute)	dB(A)	50/47/43/35/32	50/47/43/35/32	53/50/47/43/36	54/51/48/44/40
	PREISION SONORA(S/H/M/L/Mute)	dB(A)	40/37/33/25/22	40/37/33/25/22	43/41/38//35/27	44/41/38/34/30
	CAUDAL DE AIRE	m3/h	1700	1700	2600	3000
AREA DE APLICACIÓN		m2	9~16	14~22	20~35	27~45
LONGITUD MAX TUBO REFRIGERANTE		m	25	25	25	25
DIFERENCIAL MAXIMO DE NIVE		m	10	10	10	10
RANGO TEMP DE FUNCIONAMIENTO		°C	16-31	16-31	16-31	16-31
TEMPERATURA AMBIENTE	EXTERIOR	°C	Cooling:-15-53/Heating:-20-30	Cooling:-15-53/Heating:-20-30	Cooling:-15-53/Heating:-20-30	Cooling:-15-53/Heating:-20-30
	INTERIOR	°C	Cooling:17-32/Heating:0-30	Cooling:17-32/Heating:0-30	Cooling:17-32/Heating:0-30	Cooling:17-32/Heating:0-30
DIMENSIONES NETAS	INTERIOR	mm	698x255x190	777x250x201	910x294x206	1010x315x220
	AN*AL*PR	mm	712x276x459	712x276x459	853x602x349	920x699x380
PESO NETO	INTERIOR	Kg	6,5	7,5	10	13
	EXTERIOR	Kg	22	22	35	40
DIMENSIONES NETAS	INTERIOR	mm	764x325x257	840x315x260	979x372x277	1096x390x297
	AN*AL*PR	mm	765x310x481	765x310x481	890x628x385	960x732x400
PESO BRUTO	INTERIOR	Kg	8,5	10	13	16
	EXTERIOR	Kg	24(w/o pipe)25(w/i pipe)	24(w/o pipe)25(w/i pipe)	38(w/o pipe)39(w/i pipe)	43(w/o pipe)46(w/i pipe)
CONEXIONES TUBERIA	GAS	Pulg	3/8"	3/8"	3/8"	1/2"
	LIQUIDO	pulg	1/4"	1/4"	1/4"	1/4"
CARGA CAMION COMPLETO	UNIDADES POR CAMION		240	240	180	180

