## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's	name	or	trade	mark:	LUTEC	
------------	------	----	-------	-------	-------	--

Supplier's address: LUTEC EUROPE NV, Herentalsebaan 425, 2160 Wommelgem Wommelgem, BE

Model identifier:	5105002125M
-------------------	-------------

Tyne	οf	liσht	sourc	۵.
IVDE	UI.	HEIIL	Souit	┖.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	Welding		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No
		_	

## **Product parameters**

Parameter		Value	Parameter	Value
General product parameters:				
	mption in on- 100 h), rounded st integer	20	Energy efficiency class	Е
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	2 110 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode pressed in W	oower (P <sub>on</sub> ),	19,1	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	12	Spectral power	See image
dimensions	Width	51	distribution in the	in last page
without	Depth	99		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load			
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	132		
		Chromaticity	0,380		
		coordinates (x and y)	0,380		
Parameters for LED and OLED li	Parameters for LED and OLED light sources:				
R9 colour rendering index value	14	Survival factor	1,00		
the lumen maintenance factor	0,96				
Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		If yes then replacement claim (W)	-		
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	1,0		

(a)'-': not applicable;

(b)<sub>'-'</sub> : not applicable;

