

**bsl**

**DVB T2**<sup>®</sup>

**USB**  
**HDMI**

**H.265**  
**HEVC**  
High Efficiency Video Coding

**Modelo : BSL-255**

Product size	140*80*30mm
Package	40PCS/Carton
Certificate	CE,ROHS Certificate
Chipset	GX6702



USB port, RF in, HDMI, Scart, AC input con HEVC 10 MAIN H.265

**Main SPEC& Features:**

* H.265 DVB-T2 HD Receiver with GX6702 Chipset with <b>HDR 10bit</b>	* With Green or Red LED display
* Support Youtube, megogo,IPTV, RSS, Weather etc....	* Lan port Option
* Fully supports DVB-T2/T/C, H.265, H.264,HD MPEG 2, MPEG4 Decoder	* 4: 3PS、4: 3LB、16: 9
* Supports 720P,1080i,1080P(FULL HD)	* E-AC3+ function is include
* USB 2.0, Media player for H.265,H.264,AVI, MKV, MP3, MP4, JPEG etc..	* Scart Port include
* PVR, Schedule recording	* Supports updating software by USB
* Multi-language OSD	* 7 days EPG
* Support HEVC H.265 HDR 10Bit	* Banner-- time & transparency control ability
* Support H.264,H.265 & MPEG-2/MPEG4 8bit/10bit	* Display of signal strongness & quality
* TV Format: PAL, NTSC, PAL-M,	* Powerful channel editor functions
* Time shift function	* Automatic or manual Area serching
* I/O ports: RF in, HDMI, SCART, USB input ,AC input	* Full function Remote Controller.

**Main system**

CPU	<b>GX6702</b>
Flash Memory	512M bites
SDRAM	32M bites
Tuner	R850 or 836

**Audio/video data in/out**

Salidas:	<b>SCART</b>
	<b>HDMI</b>
	<b>USB</b>

**Tuner & Demodulator**

ANT. Connecto	IEC TYPE, female
Loop Outpur	Without
Input range	170~230MHz ,470~860MHz
Input Impedan	75 Ω
Input Signal lev	78 dBm to -20 dBm (average power)
IF Bandwidth	7MHz and 8MHz

**Power supply**

Input voltage:	100-240V,50-60HZ
Consumption:	Max. 6W
Protection:	Separate fuse & chassis ground or electric shock protection

**Mpeg Audio/ Vedio Decocding**

Video	MPEG 2(ISO/IEC 13818-2)
	MPEG-4 (ISO/IEC14496)
	H.264 (ISO/IEC14496-10)
	H.265 main profile level 4.1, support 8bit/10bit
Profile Level	HD MPEG 2, MPEG4 HP@L4, MP@L3
	MPEG-4 ASP D1(720*480*30/720*576*25)

**Operation Enviroment:**

Operation tempreture :	+5℃~55℃
Storage tempreture:	-40℃~ +65℃

**Dimension**

Input rate	Max. 60M bits	Size (W*D*H):140*80*30mm
Aspect ratio	4:3, 16:9, letter box	Gift box:170*135*40mm
Video Resoluti	480i/576i /720P/1080i/1080P(FULL HD)	Carton:430*360*290mm 40PCS/Carton
Audio decodin	MPEG-1(Layer1&2&3)/,MP3	N.W:11.4KG G.W:12.1KG
Audio mode	Mono/Joint Stereo/Stereo/E-AC3+ Dolby Function	Loading container:24960PCS/20GP