
Datenblatt

gültig ab: 27.08.24



JRG LegioStop Verteilbatterie komplett Rotguss

- Temperatur: max. 30°C
- Werkstoff: Rotguss, Edelstahl, EPDM, Kunststoff
- Auslieferzustand: Druckminderer 400 kPa (4 bar) Einstellbereich 200 - 600 kPa (2 - 6 bar), Sicherheitsventil 600 kPa (6 bar)
- Anschluss: Aussengewinde
- Bestehend aus: Batterieventil JRGUSIT NG 5151, JRGURED Combi 1353, Verteilarmatur JRGUSIT Combi 5191.

*Auslauf mit Ersatz

	DN-DN-DN-DN (mm)	DN (mm)	Zoll (inch)	JRG Code	NPK	GF Code	NPK	SP	Gewicht (kg)
*	25-20-25-25	25	1	**1521.400**		**355 623 538**		1	7.665
*	32-20-25-25	32	1 ¼	**1521.480**		**355 623 548**		1	8.235

	DN-DN-DN-DN (mm)	d1 G (inch)	d2 G (inch)	d3 G (inch)	d4 Rp (inch)	d4 G (inch)	d5 Rp (inch)	d6 Rp (inch)	d7 G (inch)	d8 G (inch)	d9 G (inch)	d10
*	25-20-25-25	1 ¼	1	1 ¼	¾	¾	¾	¼	¾	1	½	TR 30 x 1.5
*	32-20-25-25	1 ½	1	1 ¼	¾	¾	¾	¼	¾	1	½	TR 30 x 1.5

	DN-DN-DN-DN (mm)	h1 (mm)	h2 (mm)	h3 (mm)	l (mm)	l1 (mm)	l2 (mm)	l3 (mm)	l4 (mm)	l5 (mm)	l6 (mm)	PN (bar)
*	25-20-25-25	55	77	390	586	37	133	93	145	130	48	16
*	32-20-25-25	56	77	393	618	42	149	104	145	130	48	16

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com