

XLED Home 2

The evolution of success story.

- With a light output of 1184 lm
- Low power consumption of 14.8 W
- With integrated infrared sensor
- Fully turnable LED Panel
- 4000K and opal disk for maximum light comfort
- New elegant design
- Available in colours - white, silver, black and graphite



XLED Home 2

The evolution of success story.

Technical Data

Dimensions (LxBxH): 194 x 180 x 161 mm
 Voltage: 230-240V, 50/60 Hz
 Power: 14.8 W
 Light output/Efficiency: 1184 lm, 80 lm/W
 Light colour: 4000K neutral white / SDCM 3
 LED-Lifetime: 50,000 h (L70B10)
 Colour Rendering Index: Ra > 80
 Sensor Technology: Passiv Infrared
 Detection angle: 140°
 Detection range: 14 m
 IP-/Protection class: IP 44 / II
 Material: UV-resistant plastic (Chassis), Thermo conductive plastic (Heat sink)

Customs tariff number: 94051040
 Country of origin: Germany (Production start), Romania (Serial production)
 Region of origin: 14 (Production start), 03 (Serial production)



EAN-Code	Art.-No.	Bezeichnung Description
4007841 033088	033088	LED Floodlight XLED Home 2 white
4007841 033071	033071	LED Floodlight XLED Home 2 black
4007841 033064	033064	LED Floodlight XLED Home 2 graphite
4007841 033057	033057	LED Floodlight XLED Home 2 silver