

MG7000E+CONTROL REMOTO

7000W 230V



REMOTE CONTROL START UP
ARRANQUE POR CONTROL REMOTO

TIPO / TYPE



EQUIPAMIENTO / FEATURES



DOTACION / INCLUDED



EMBALAJE / PACKAGING



MODELO / MODEL

Regulación - Voltaje - Frecuencia / Regulation - Voltage - Frequency

AC 230V Máxima / Maximum

AC 230V Nominal / Rated

Modelo motor/ Engine model

Cilindrada/ Displacement

Tipo de motor / Engine type

Nivel de presión acústica media a 7Mts LpA / Acoustic pressure level average at 7Mts LpA

Nivel de potencia acústica garantizada LWA acorde 2000/14/EC enmienda 2005/88/EC

Guaranteed sound power level LWA pursuant to 2000/14/EC amended by 2005/88/EC

Tipo de arranque / Startup type

Capacidad tanque combustible / Fuel tank capacity

Consumo hora - Autonomía al 25%, 50%, 75% carga

Hourly consumption - Autonomy at 25%, 50%, 75% loads

Capacidad de aceite - Tipo aceite / Oil capacity - Type of oil

Kit de transporte / Transportation kit

Dimensiones

Peso máquina / bruto embalaje (Kg) / Machine weight / gross packaging (Kg)

Referencia / Reference

RECAMBIOS FRECUENTES / FREQUENT SPARE PARTS



Ref. 4000001



Ref. 4000064



Ref. 4000010



Ref. 4000057

MG7000E E-START + REMOTE CONTROL

Estabilizador electrónico / Electronic stabilizer - 230V - 50Hz

7000W

6500W

GENERGY SGB420

420cc

Gasolina, 4 tiempos OHV refrigeración forzada por aire

Gasoline, 4-stroke OHV, air forced cooling

74dB (A)

97dB (A)

Manual-eléctrico-remoto / recoil-electric-remote

21L

(1.6 l/h - 13h) (1.9 l/h - 11h) (2.5 l/h - 8.4h)

1.1L SAE10W30 - SAE10W40

Si

Yes

69X52X56

83/88

14525