


<b>MODELO / MODEL</b>		<b>ASTON WHITE MT</b>		
<b>FOTO / PICTURE (ORIENTATIVE)</b>				
<b>FORMATO / SIZE</b>		<b>60 X 60 cms.apprx. RECT.</b>		
<b>GRUPO / GROUP</b>		<b>Bla</b>		
<b>TIPO / TYPE</b>		<b>PORCELANICO ESMALTADO / Glazed Porcelain Tile</b>		
<b>DESCRIPCION DEL TEST / TEST DESCRIPTION</b>		<b>VALOR DEL TEST / TEST VALUE</b>	<b>KERATILE</b>	<b>NORMA / STANDARD</b>
<b>ABSORCIÓN DE AGUA / WATER ABSORPTION</b>		AA < 0,5%	<b>Cumple / Passed</b>	UNE-EN-ISO 10545-3
<b>FUERZA DE ROTURA / BREAKING STRENGTH</b>		> 1300 N	<b>Cumple / Passed</b>	UNE-EN-ISO 10545-4
<b>RESISTENCIA A LA FLEXIÓN / RESISTANCE OF FLEXION</b>		> 35 N/mm2	<b>Cumple / Passed</b>	UNE-EN-ISO 10545-4
<b>ABRASION SUPERFICIAL / SURFACE ABRASION</b>		Clase / Class	<b>PEI IV</b>	UNE-EN-ISO 10545-7
<b>RESISTENCIA AL CUARTEO / CRACKING RESISTANCE</b>		Requerido / Requested	<b>Cumple / Passed</b>	UNE-EN-ISO 10545-11
<b>RESISTENCIA A LA HELADA / FROST RESISTANCE</b>		Requerido / Requested	<b>Cumple / Passed</b>	UNE-EN-ISO 10545-12
<b>RESISTENCIA QUIMICA / CHEMICAL RESISTANCE</b>	<b>(PRODUCTOS DOMESTICOS Y DE PISCINA / Domestic &amp; Swimming Pool Products)</b>	Mínimo / Minimum GB	<b>Cumple / Passed</b>	UNE-EN-ISO 10545-13
<b>RESISTENCIA A LOS ACIDOS / ACID RESISTANCE</b>		GHA	<b>Cumple / Passed</b>	UNE-EN-ISO 10545-13
<b>RESISTENCIA A LAS BASES / ALKALINE RESISTANCE</b>		GHA	<b>Cumple / Passed</b>	UNE-EN-ISO 10545-13
<b>RESISTENCIA A LAS MANCHAS / RESISTANCE TO STAINS</b>		Mínimo / Minimum Class 3	<b>Cumple / Passed</b>	UNE-EN-ISO 10545-14
<b>SLIP RESISTANCE</b>		Available Method	<b>R9</b>	DIN 51130:2014-5
<b>RESISTENCIA AL DESLIZAMIENTO / SLIP RESISTANCE</b>		Metodo Disponible / Available Method	<b>Class 1</b>	UNE-ENV 12633:2003
<b>RESISTENCIA AL RAYADO / HARDNESS (MOHS)</b>		Mínimo / Minimum 3	<b>Cumple / Passed</b>	EN 101

**KERATILE S.L.U.**

CIF B-12943338

Calle del Ferrocarril, 4

12593 Moncofa (Castellon) Spain

Tel. +34 964 584 069 - Fax +34 964 584 070