


<b>MODELO / MODEL</b>		<b>Nanotech SERIE SANFORD MT</b> (WHITE, GREY, NATURAL, BROWN)		
<b>FOTO / PICTURE (ORIENTATIVE)</b>				
<b>FORMATO / SIZE</b>		30 X 150 cms.apprx. RECT.		
<b>GRUPO / GROUP</b>		Bla		
<b>TIPO / TYPE</b>		PORCELANICO ESMALTADO / Glazed Porcelain Tile		
<b>DESCRIPCION DEL TEST / TEST DESCRIPTION</b>		<b>VALOR DEL TEST / TEST VALUE</b>	<b>KERATILE</b>	<b>NORMA / STANDARD</b>
ABSORCIÓN DE AGUA / WATER ABSORPTION		AA < 0,5%	Cumple / Passed	UNE-EN-ISO 10545-3
FUERZA DE ROTURA / BREAKING STRENGTH		> 1300 N	Cumple / Passed	UNE-EN-ISO 10545-4
RESISTENCIA A LA FLEXIÓN / RESISTANCE OF FLEXION		> 35 N/mm2	Cumple / Passed	UNE-EN-ISO 10545-4
ABRASION SUPERFICIAL / SURFACE ABRASION		Clase / Class	WHITE, GREY PEI IV NATURAL, BROWN PEI III	UNE-EN-ISO 10545-7
RESISTENCIA AL CUARTEO / CRACKING RESISTANCE		Requerido / Requested	Cumple / Passed	UNE-EN-ISO 10545-11
RESISTENCIA A LA HELADA / FROST RESISTANCE		Requerido / Requested	Cumple / Passed	UNE-EN-ISO 10545-12
RESISTENCIA QUIMICA / CHEMICAL RESISTANCE	(PRODUCTOS DOMESTICOS Y DE PISCINA / Domestic & Swimming Pool Products)	Minimo / Minimum GB	Cumple / Passed	UNE-EN-ISO 10545-13
RESISTENCIA A LOS ACIDOS / ACID RESISTANCE		GHA	Cumple / Passed	UNE-EN-ISO 10545-13
RESISTENCIA A LAS BASES / ALKALINE RESISTANCE		GHA	Cumple / Passed	UNE-EN-ISO 10545-13
RESISTENCIA A LAS MANCHAS / RESISTANCE TO STAINS		Minimo / Minimum Class 3	Cumple / Passed	UNE-EN-ISO 10545-14
RESISTENCIA AL DESLIZAMIENTO / SLIP RESISTANCE		Metodo Disponible / Available Method	Class 3	UNE-ENV 12633:2003
RESISTENCIA AL RAYADO / HARDNESS (MOHS)		Minimo / Minimum 3	Cumple / Passed	EN 101