

MODELO / MODEL		SERIE STEEL MT RECT. (BLANCO, GRIS, BEIGE, COBRE, GRAFITO)		
FOTO / PICTURE (orientativa)				
FORMATO / SIZE		60 x 120 cms. Rect.		
GRUPO / GROUP		Bla		
TIPO / TYPE		PORCELANICO ESMALTADO / Glazed Porcelain Tile		
DESCRIPCION DEL TEST / TEST DESCRIPTION		VALOR DEL TEST / TEST VALUE	KERATILE	NORMA / STANDARD
ABSORCIÓN DE AGUA / WATER ABSORPTION		AA < 0,5%	Cumple / Passed	UNE-EN-ISO 10545-3
FUERZA DE ROTURA / BREAKING STRENGTH		> 1300 N	Cumple / Passed	UNE-EN-ISO 10545-4
RESISTENCIA A LA FLEXIÓN / RESISTANCE OF FLEXION		> 35 N/mm2	Cumple / Passed	UNE-EN-ISO 10545-4
ABRASION SUPERFICIAL / SURFACE ABRASION		Clase / Class	BLANCO, GRIS, BEIGE PEI IV / COBRE, GRAFITO PEI III	UNE-EN-ISO 10545-7
RESISTENCIA AL CUARTEO / CRACKING RESISTANCE		Requerido / Requested	Cumple / Passed	UNE-EN-ISO 10545-11
RESISTENCIA A LA HELADA / FROST RESISTANCE		Requerido / Requested	Cumple / Passed	UNE-EN-ISO 10545-12
RESISTENCIA QUIMICA / CHEMICAL RESISTANCE	(PRODUCTOS DOMESTICOS Y DE PISCINA / Domestic & Swimming Pool Products)	Mínimo / Minimum GB	Cumple / Passed	UNE-EN-ISO 10545-13
RESISTENCIA A LOS ACIDOS / ACID RESISTANCE		GHA	Cumple / Passed	UNE-EN-ISO 10545-13
RESISTENCIA A LAS BASES / ALKALINE RESISTANCE		GHA	Cumple / Passed	UNE-EN-ISO 10545-13
RESISTENCIA A LAS MANCHAS / RESISTANCE TO STAINS		Mínimo / Minimum Class 3	Cumple / Passed	UNE-EN-ISO 10545-14
RESISTENCIA AL DESLIZAMIENTO / SLIP RESISTANCE		Metodo Disponible / Available Method	Class 1	UNE-ENV 12633:2003
RESISTENCIA AL RAYADO / HARDNESS (MOHS)		Mínimo / Minimum 3	Cumple / Passed	EN 101