

| Datos técnicos | | Unidades | Climate RAC 5000 2,6-2 R32 | Climate RAC 5000 3,5-2 R32 | Climate RAC 5000 5,3-2 R32 | Climate RAC 5000 7,0-2 R32 |
|---|--------------------------------|----------|--|--|---|--|
| Capacidad Frío | kW/h | | 2,6 (0,9 - 3,4) | 3,5 (1,1 - 4,2) | 5,3 (1,8 - 6,1) | 7,0 (2,7 - 7,9) |
| | Kcal/h | | 2268 (756-2923) | 3024 (958-3578) | 4536 (1562-5267) | 6048 (1789-6834) |
| Capacidad Calor | kW/h | | 2,9 (0,8 - 3,4) | 3,8 (1,1 - 4,2) | 5,6 (1,4 - 6,7) | 7,3 (1,6 - 8,8) |
| | Kcal/h | | 2579 (688-3095) | 3439 (757-3783) | 4987 (963-5847) | 6048 (2175-6535) |
| Consumo Frío | W | | 710 (100 - 1240) | 1237 (130 - 1580) | 1539 (140 - 2360) | 2345 (160 - 2960) |
| Consumo Calor | W | | 739 (120 - 1200) | 964 (100 - 1580) | 1480 (200 - 2410) | 2035 (260 - 3140) |
| Frío estacional | SEER (Etiqueta) | W/W | 6,2 (A ^{**}) | 6,1 (A ^{**}) | 7,1 (A ^{**}) | 6,1 (A ^{**}) |
| Calor (clima cálido /medio) | SCOP (Etiqueta) | W/W | 4,9 (A ^{**})/4,0 (A [*]) | 4,6 (A ^{**})/4,0 (A [*]) | 5,2 (A ^{***})/4,0 (A [*]) | 5,0 (A ^{**})/4,0 (A [*]) |
| Espectro ErP | | | A ^{***} →D | A ^{***} →D | A ^{***} →D | A ^{***} →D |
| Allimentación | V-Hz | | 220-240V-50Hz | 220-240V-50Hz | 220-240V-50Hz | 220-240V-50Hz |
| Unidades interiores | | | Climate RAC 5000 2,6-3 IBW | Climate RAC 5000 3,5-3 IBW | Climate RAC 5000 5,3-3 IBW | Climate RAC 5000 7-3 IBW |
| Nivel de presión sonora (Si/Bajo/Medio/Alto) | dB(A) | | 21/26/30/40 | 22/26/34/40 | 25/30/37/44 | 28/35/42/45 |
| Dimensiones (Ancho x Profundo x Alto) | mm | | 805x194x285 | 805x194x285 | 957x213x302 | 1040x220x327 |
| Peso Neto/Bruto | Kg | | 7,6/9,7 | 7,6/9,7 | 10,0/13,0 | 12,3/15,8 |
| Unidades exteriores | | | Climate RAC 5000 2,6-2 OUE | Climate RAC 5000 3,5-2 OUE | Climate RAC 5000 5,3-2 OUE | Climate RAC 5000 7-2 OUE |
| Caudal de aire | m3/h | | 1700 | 1700 | 2500 | 3000 |
| Nivel de presión sonora | dB(A) | | 56 | 56 | 56 | 60 |
| Dimensiones (Ancho x Profundo x Alto) | mm | | 700x275x550 | 700x275x550 | 800x333x554 | 845x363x702 |
| Peso Neto/Bruto | Kg | | 22,8/25,2 | 22,7/25,2 | 34,0/36,7 | 51,5/54,5 |
| Refrigerante | Tipo | | R32 | R32 | R32 | R32 |
| | GWP | | 675 | 675 | 675 | 675 |
| | Cantidad carga | Kg | 0,5 | 0,5 | 1,0 | 1,6 |
| | Equivalente de CO ₂ | Ton | 0,338 | 0,338 | 0,675 | 1,080 |
| | Distancia estándar | m | 5 | 5 | 5 | 5 |
| | Carga adicional | g/m | 12 | 12 | 12 | 24 |
| Tubería refrigerante | Líquido / Gas | pulg. | 1/4"-3/8" | 1/4"-3/8" | 1/4"-1/2" | 3/8"-5/8" |
| | Máx. Longitud | m | 25 | 25 | 30 | 50 |
| | Máx. Vertical | m | 10 | 10 | 20 | 25 |

(1) Precio base de venta. IVA no incluido.
 Contiene gas refrigerante R32 con GWP = 675.