

Movement detector IS 360-1 DE

STEINEL inside. Intelligent technology for installation.

- 360° detection angle with 4m detection range
- IR-sensor für canopies and recessed ceilings
- Intelligent hidden installation possibilities
- Manual Override Function
- Restriction of detection areas using cover plates



Movement detector IS 360-1 DE

STEINEL inside. Intelligent technology for installation.

Technical Data

Dimensions (Ø x H):	Ø78 x 89 mm
Voltage:	230-240V, 50/60 Hz
Sensor-Technology:	Passiv-Infrared
Installation area:	outdoors and indoors
Detection angle:	360°
Detection range:	Max. 4 m
Switching capacity:	max. 1000 W (ohmic loads, i.e. all incandescent lamps) max. 6 (electronic ballast/ LED lamps) C ≤ 132 µF
Twilight settings:	2 - 2000 Lux
Time settings:	8 sec. – 35 min.
IP-/Protection class:	IP 54 / II
Material:	UV-resistant plastic
Accessories:	Cover plate
Customs tariff number:	85365080
Country of origin:	Switzerland (Production start), Romania (Serial production)
Region of origin:	SZ (Production start), 03 (Serial production)



EAN	Art.-No.	Bezeichnung Description
4007841 032845	032845	Movement detector IS 360-1 DE white
4007841 032852	032852	Movement detector IS 360-1 DE black