

Combi-Safety accessories (aluminium)

Step / Tray

- + Suitable for ladders with rungs for more safety and comfort
- + Usable as a tray for all kind of items when working on rung ladders
- + Loadable up to 150 kg
- + TÜV-approved





Ladder spikes (Pair)

- According to the accident prevention regulations of the Employers' Liability Insurance Association ladders must be equipped with ladder spikes when used on natural soft ground
- + Also usable on ladders with stabilisers
- + Suitable for side rails with a width of 64 x 25 mm to 97 x 25 mm
- + TÜV-approved





ArtNo
122063

Side rail extension

- + To compensate height differences such as stairs, curbsides etc.
- + Infinitely adjustable up to max. 400 mm
- + Suitable for side rails with a width of 64 x 25 mm to 97 x 25 mm
- + TÜV-approved



Spacer device

+ Usable in areas with difficult access e.g. ledges, overhanging roofs etc.

Art.-No. 121400

- + Telescopic supports, extendable up to 600 mm
- + Suitable for side rails with a width of 64 x 25 mm to 97 x 25 mm
- + TÜV-approved





ArtNo.
122292

Stabiliser

- + To compensate height differences up to 17 cm on stairs/ledges etc.
- + Suitable for side rails with a width of 64 x 25 mm to 97 x 25 mm
- + Length approx. 1.250 mm
- + TÜV-approved





Cross rail leveller

 + To compensate height differences when using stabilisers on stairs, ledges or uneven ground for a maximum of stability (extension range up to 230 mm)

Art.-No. 122018

- + Suitable for all ladders with stabilisers (excepting multipurpose ladder \(\rangle \) 3x6 rungs as trestle with extended third ladder part)
- + TÜV-approved



121417

Hinged ladder platform set

- + To be used in combination with multipurpose hinged ladders to create a working platform or a placement area
- + Slip-resistant and waterproof working platform suitable for a max. load of 150 kg





Ladder wall holder set

- For safe and space-saving storage of ladders with rungs
- + Lockable (lock not included)
- + Internal dimensions: approx. 270 x 150 mm

Art.-No.





ArtNo.
122261

