



Catalogue Heaters 2020





B990298X | EAN 9008505065242 | electric fireplace

technical details

- two heating levels 1750W/2000W
- voltage 220V-240V ~ 50 Hz
- adjustable flame effect
- LED (2x1W 90lm)
- Timer
- Remote control & panel switch
- MDF Frame
- color: white
- GS certified
- TÜV certified
- CE certified

Measurement (L/H/W) in cm:

Frame: 109x100x26

Heater: 52,5x59,2x16,3



B991333D | EAN 9008505075722 | electric fireplace

technical details

- Dimplex heater
- main voltage 230V ~ 50 Hz
- flame effect 180W (4Ct./h)
- flame regulation
- thermostat
- 0/flame/1000/2000 W heating steps
- real log flame effect
- MDF frame
- color: white
- with remote control

- overheating protection
- mirror effect
- GS certified
- TÜV certified
- CE certified
- cable length app. 1,5m

Measurements (L/H/W) in cm:

Frame: 87x90x30

Heater: 70x65x27



BG00559 | EAN 9008505089262 | electric fireplace

technical details

- main voltage 220V-240V ~ 50 Hz
- 220V - 1750W, 230V - 1800 W, 240V - 2000W
- two heating steps
- flame effect offers four different levels
- flame effect can be used independently
- timer range from 30 minutes to 7.5 hours
- two pin round VDE plug
- real log flame
- wooden frame
- color: white
- with remote control and manual control panel
- LED light

Measurements (L/H/W) in cm:
88x85x30



B991541 | EAN 9008505073209 | electric fireplace

technical details

- main voltage 220V-240V ~ 50 Hz
- two heating steps 750W/1500W
- flame effect offers four different levels
- timer range from 30 minutes to 7.5 hours
- real log flame- wooden frame
- color: white
- with remote control and manual control panel
- overheat protection
- LED light

Measurements (L/H/W) in cm:
frame: 100x96x25
heater: 44,8x62,4x16,5



B991570 | EAN 9008505072738 | electric fireplace

technical details

- main voltage 220V-240V ~ 50 Hz
- 1400W-1600W
- two heating steps
- flame effect offers four different levels
- timer range from 30 minutes to 7.5 hours
- electronic timer
- color: white
- MDF frame with drawer
- with remote control and manual control panel
- overheating protection
- LED light

Measurements (L/H/W) in cm:
frame: 101x100x21,7
heater: 58,5x47x18



B991901 | EAN 9008505080337 | electric fireplace

technical details

- main voltage 220V-240V ~ 50 Hz
- 1750W/2000W
- two heating steps
- flame effect offers four different levels
- timer range from 30 minutes to 7.5 hours
- LED 2x1W 90lm
- color: white / natural
- MDF frame with drawer
- with remote control and manual control panel
- overheating protection
- CE, GS and TÜV certificate

Measurements (L/H/W) in cm:
frame: 120x110x26
heater: 52,5x59,2x16,3



B991602 | EAN 9008505074244 | electric fireplace

technical details

- main voltage 220V-240V ~ 50 Hz
- two heating steps 950W/1900W
- flame effect adjustable
- crystal frame
- MDF outline
- mirror
- with remote control and manual control panel
- CE certificate

Measurements (L/H/W) in cm:
frame: 105x100x32
heater: 53x59,2x16



B992176 | EAN 9008505088494 | electric fireplace

technical details

- main voltage 230V ~ 50 Hz
- two heating steps 950W/2000W
- flame effect adjustable
- cement look
- MDF outline
- real log flame effect
- with remote control and manual control panel
- LED light

Measurements (L/H/W) in cm:
85x95x25



B991331-3 | EAN 9008505063941 | electric fireplace

technical details

- main voltage 230V ~ 50 Hz
- two heating steps 1400W/1600W
- flame effect adjustable on four levels
- color: white
- MDF frame
- with remote control and manual control panel
- timer ranges from 30 minutes to 7.5 hours
- LED light

Measurements (L/H/W) in cm:
frame: 100x90x24
heater: 74,3x53,4x24,5



B991331-15 | EAN 9008505064351 | electric fireplace

technical details

- main voltage 230V ~ 50 Hz
- two heating steps 1400W/1600W
- flame effect adjustable on four levels
- color: grey
- MDF frame
- with remote control and manual control panel
- timer ranges from 30 minutes to 7.5 hours
- LED light

Measurements (L/H/W) in cm:
frame: 100x90x24
heater: 74,3x53,4x24,5



B992248 | EAN 9008505110096 | electric fireplace

technical details

- main voltage 220V ~ 50 Hz
- two heating steps 750W/1500W
- flame effect adjustable on four levels
- color: grey
- MDF frame
- overheating protection
- thermostat
- ERP remote control with LCD display
- 7 day timer
- LED light

Measurements (L/H/W) in cm:
120x67x26



B992077 | EAN 9008505085417 | electric fireplace

technical details

- main voltage 220V -240V ~ 50 Hz
- two heating steps 1750W/2000W
- flame effect adjustable
- color: high gloss white
- flat panel with flat stonefoil
- MDF frame
- overheating protection
- timer
- ERP remote control and manual control panel
- 7 day timer
- LED light

Measurements (L/H/W) in cm:
120x25,5x61



B992078 | EAN 9008505085424 | electric fireplace

technical details

- main voltage 220V -240V ~ 50 Hz
- two heating steps 1750W/2000W
- flame effect adjustable
- color: high gloss white
- flat panel with flat stonefoil
- MDF frame
- overheating protection
- timer
- ERP remote control and manual control panel
- 7 day timer
- LED light

Measurements (L/H/W) in cm:
120x25,5x61



B991348 | EAN 9008505064115 | electric fireplace

technical details

- main voltage 220V-240V ~ 50 Hz
- two heating steps 750W/1500W
- flame effect adjustable on 4 levels
- color: black
- for wall mounting
- remote control
- timer from 30 minutes to 7.5 hours
- LED light
- overheating protection
- GS, CE certified

Measurements (L/H/W) in cm:
99,7x71x12,5



B991580-3 | EAN 9008505072769 | electric fireplace

technical details

- main voltage 220V-240V ~ 50 Hz
- two heating steps
- 1400W-1600W
- flame effect adjustable
- brightness adjustment
- color: white
- for wall mounting or floor standing
- remote control and control panel
- timer from 30 minutes to 7.5 hours
- LED light 8x1W 90lm
- overheating protection
- GS, CE and TÜV certified

Measurements (L/H/W) in cm:
128x61x26



B991580-4 | EAN 9008505072776 | electric fireplace

technical details

- main voltage 220V-240V ~ 50 Hz
- two heating steps
- 1400W-1600W
- flame effect adjustable
- brightness adjustment
- color: black
- for wall mounting or floor standing
- remote control and control panel
- timer from 30 minutes to 7.5 hours
- LED light 8x1W 90lm
- overheating protection
- GS, CE and TÜV certified

Measurements (L/H/W) in cm:
128x61x26



B991848-4 | EAN 9008505078723 | electric fireplace

technical details

- main voltage 220V-240V ~ 50 Hz
- two heating steps
- 1400W-1600W
- flame effect adjustable on 4 levels
- color: black
- glass stand
- for wall mounting or floor standing
- remote control and control panel
- timer from 30 minutes to 7.5 hours
- LED light 6x1W 90lm
- overheating protection
- GS, CE and TÜV certified

Measurements (L/H/W) in cm:
84x50,9x26



B991849-3 | EAN 9008505078754 | electric fireplace

technical details

- main voltage 220V-240V ~ 50 Hz
- two heating steps
- 1400W-1600W
- flame effect adjustable on 4 levels
- color: white
- glass stand
- for wall mounting or floor standing
- remote control and control panel
- timer from 30 minutes to 7.5 hours
- LED light 4x1W 90lm
- overheating protection
- GS, CE and TÜV certified

Measurements (L/H/W) in cm:
60x50,9x26



B991849-4 | EAN 9008505078747 | electric fireplace

technical details

- main voltage 220V-240V ~ 50 Hz
- two heating steps
- 1400W-1600W
- flame effect adjustable on 4 levels
- color: black
- glass stand
- for wall mounting or floor standing
- remote control and control panel
- timer from 30 minutes to 7.5 hours
- LED light 4x1W 90lm
- overheating protection
- GS, CE and TÜV certified

Measurements (L/H/W) in cm:
60x50,9x26



BG00519 | EAN 9008505089309 | electric fireplace

technical details

- main voltage 220V-240V ~ 50/60 Hz
- two heating steps 1000W/2000W
- flame effect adjustable on 4 levels
- frame: stainless steel
- background & flames changeable, 7 colors
- flame effect individually switchable and adjustable
- remote control
- overheating protection

Measurements (L/H/W) in cm:
90x60x26



B991850-4 | EAN 9008505078761 | electric fireplace

technical details

- main voltage 220V-240V ~ 50/60 Hz
- two heating steps 900W/1800W
- flame effect can be used independently
- flame effect adjustable
- frame: tempered glass, black, curved
- remote control
- overheating protection
- LED 4x1W 85lm

Measurements (L/H/W) in cm:
65x56x26



B991899-3 | EAN 9008505080306 | electric fireplace

technical details

- main voltage 220V-240V ~ 50/60 Hz
- two heating steps 1000W/2000W
- campfire effect
- flame effect adjustable
- frame: tempered glass, white, curved
- white plastic stand
- remote control and manual control panel
- overheating protection

Measurements (L/H/W) in cm:
66x58x21



B991899-4 | EAN 9008505080313 | electric fireplace

technical details

- main voltage 220V-240V ~ 50/60 Hz
- two heating steps 1000W/2000W
- campfire effect
- flame effect adjustable
- frame: tempered glass, black, curved
- white plastic stand
- remote control and manual control panel
- overheating protection

Measurements (L/H/W) in cm:
66x58x21



B992024 | EAN 9008505083086 | electric fireplace

technical details

- main voltage 220V-240V ~ 50/60 Hz
- two heating steps 900W/1800W
- patent LED flame design
- wood fuel effect
- flame effect adjustable
- flame effect can be used independently
- frame: tempered glass, black, curved
- plastic stand
- overheating protection

Measurements (L/H/W) in cm:
66x58x21



B990450-1 | EAN 9008505072059 | electric fireplace

technical details

- main voltage 220V-240V ~ 50 Hz
- two heating steps 1750W/1950W
- flame effect adjustable
- color: white
- manual switch
- overheating protection
- TÜV certified, GS certified
- LED light 3x1W 90lm

Measurements (L/H/W) in cm:
42x56,5x25,5



B991502 | EAN 9008505070666 | electric fireplace

technical details

- main voltage 220V-240V ~ 50 Hz
- two heating steps 950W/1950W
- real log flame effect
- door can be opened
- color: black
- remote control
- overheating protection
- normal plug
- LED bar

Measurements (L/H/W) in cm:
50x73,5x32



B991505 | EAN 9008505072707 | electric fireplace

technical details

- main voltage 220V-240V ~ 50 Hz
- two heating steps 1000W/2000W
- real log flame effect
- flame effect can be used separately
- freestanding or mobile style
- castors for easy movement
- black metal cabinet
- overheating protection
- LED 3x1W 85lm

Measurements (L/H/W) in cm:
43x62,5x27,5



BG00595 | EAN 9008505113561 | electric fireplace

technical details

- main voltage 220V-240V ~ 50 Hz
- 1800W/2100W
- two heating steps 1000W/2000W
- real log flame effect
- flame effect can be used separately
- black cast effect finish
- patented LED flame
- overheating protection

Measurements (L/H/W) in cm:
44,5x74,4x34,4



BG00425 | EAN 9008505081273 | heater

technical details

- main voltage 220V-240V ~ 50/60 Hz
- 2000W
- two heating steps 1250W/2000W
- rotary power switch
- adjustable thermostat control
- overheating protection

Measurements (L/H/W) in cm:
62x39x26



BG00433 | EAN 9008505089323 | ceramic heater

technical details

- 2000W
- metal housing
- carry handle
- plastic base
- H05VV-F 3 G0.75mm²

Measurements (L/H/W) in cm:
22,7x24x12,5



BG00465 | EAN 9008505081266 | fan heater

technical details

- heating output 25/3000W
- heating element: stainless steel
- adjustable thermostat control
- overheating protection
- with fan
- full metal casing
- insulated handle
- free standing & portable type
- waterproof class IP24
- Certificates: CE/GS/LVD/EMC/RoHS

Measurements (L/H/W) in cm:
26x32x23



B991572 | EAN 9008505072721 | bar table heater

technical details

- anodized extruded aluminium alloy frame
- control box
- high efficiency carbon fire heating elements
- two power settings 800W/1600W
- 1.8 m power supply cord
- tempered glass table top D: 60cm
- stainless steel base cover D: 40cm
- height 110cm
- 360° tip-over safety switch
- IP55 approved
- cool touch coating on mesh

Measurements (L/H/W) in cm:
60x110x60