

QUA-016, rev.: 00

PORTALÁMPARAS DE BAQUELITA / BAQUELITE LAMP-HOLDER		
		
161-B	162-B	163-B
FORMA EXTERNA Y DIMENSIONES / EXTERNAL SHAPE AND DIMENSIONS	FORMA/SHAPE 161: Liso / <i>Plain</i> 162: Roscado / <i>Threaded</i> 163. Roscado con tope / <i>Threaded with stop ring.</i>	DIMENSIONES / DIMENSIONS Ø 39 x 54 mm Ø 40 x 58 mm Ø 40 X 54 mm
DIRECTIVA / DIRECTIVE	2014/35/UE REBT 2002 – Reglamento de Baja Tensión/ <i>Spanish Low Voltage Regulations</i>	
CARACTERÍSTICAS ELÉCTRICAS ELECTRICAL CHARACTERISTICS	Casquillo / Cap: Intensidad /Current: Tensión / Voltage: Frecuencia / Frequency:	E-27 4 A 250 V 50 / 60 Hz
MATERIAL	Baquelita / Baquelite	
COLOR / COLOUR	Blanco / White RAL9003	
MÉTODO DE FIJACIÓN / FIXING METHOD	Tuerca/ Nut M10 x 1,0 Con tornillo antirotación / with antirotating screw	
TIPO DE BORNE / TERMINAL TYPE	Borne con tornillo / Screw-type terminal	
RESISTENCIA DE AISLAMIENTO / ISOLATION RESISTANCE	>4 M Ω	
RIGIDEZ DIELECTRICA / DIELECTRIC STRENGTH	1500 V	
NORMAS APLICADAS / APPLIED STANDARD	EN 60238	