

Multiple socket outlet Supraline, 4-fold, with CP, with switch



- all Supraline system advantages
- stable channel profile, partially double-walled
- diagonally placed sockets - perfect for angle plugs
- sockets moulded in one piece
- hidden fixing holes on the rear side
- suspension clips can be removed
- cable exit to both ends possible
- ergonomic safety plug (angled)
- massive current contacts for high load
- cable bend protection integrated
- dimensions (WxHxD): approx. 295 x 70 x 42 mm

■ with 2-pole, illuminated control switch

■ socket with child protection

■ break proof body from special plastic

■ cable stored inside casing

■ cable: 1.9 m H05VV-F 3G1.5 mm²

■ 16 A, 250 V~, 3500 W

■ for indoor use

Art.no. **0014412113**

Description white-white

Common data

type of packing	Schiebehülle
garanty	month
customs tariff number	85444290900
EAN-Code	4006341608260

Quantites

PU	4	piece
number of PU per export board	0	piece
number of products per palett	0	piece
number of PU per board layer	0	piece
number of board layers per pale	0	piece
number of PU per palett	0	piece

Weights

weight product	644	g
weight packing	0	g
weight packed product	662	g
weight PU	2,764	kg
weight export board	0	kg
weight palett	0	kg

Dimensions

dim product	4,8x7,7x40	cm
dim. packing	4,8x7,7x40	cm
dim. PU board	42,8x19,1x8,6	cm
volume PU	7,03	dm ³
Dim. export board		cm
hight of pallet	0	cm