



PRODUCT NUMBER: 1034306
Two filters A2P3 for N5500
Twin half-mask Paints / Sprays / Varnishes

The A2P3 cartridge is part of the wide range of cartridges offered to protect against many hazardous gases, vapors and/or particulates in many applications. The Honeywell range provides high quality and a cost-effective protection. The cartridges of Honeywell range are tested against standard EN14387. Product emphasized in an effective packaging designed for a self-service environment.



Overview

Reference Number

1034306

Product Type

Respiratory Protection

Range

Reusable APR

Line

Filter

Brand

Honeywell

Brand formerly known as

NORTH

Industry

- Agriculture
- Automotive and Part Manufacturer
- Aviation
- Building and Construction
- Chemical Industries
- Foundry
- General Industry
- Glass Industries
- Green Spaces
- Industrial Cleaning
- Laboratory
- Maintenance
- Medical and Pharmaceutical
- Metal steel
- Paper Industries
- Ship Building
- Textile Industries
- Utilities
- Water treatment
- Welding
- Wood Industries

Product Use

Controls before use

Users must:

- Ensure that the level of protection offered by the respirator is sufficient for the type and concentration of contaminant(s) in the work area.
- Respect the shelf life figuring on the filter.
- Check the seal points.

Features & Benefits

Feature

Lower profile and lightweight

Benefit

Optimal comfort

Feature

Low profile

Benefit

Do not obstruct the field of vision

Feature

Threaded connector

Benefit

Easy to attach

Feature

Small opening

Benefit

Easy check up

Feature

Product delivered in a clear and effective packaging designed for a self-service environment, which provides the needed information to easily make the right protection choice. It includes pictograms to easily recognize the protection range as well as hazards identification and product advantages.

Benefit

Customers can easily recognize which personal protective equipment to choose, depending on their work environment and the risks they face. As a result, they become autonomous and can be sure they are making the right protection choice.

Certifications

EC Category PPE

3

Quality Assurance

ISO 9001 / 2000

EC Certificate Number

2259

EC Attestation

EN certificate A2-A2P3

EC Attestation Number

2259

Certifications

- EN 14387

REACH

EU Regulation 1907/2006 (REACH) Compliance	
The substance(s) listed below may be contained in this product above the threshold level of 0.1% by weight of the listed article.	
Product Reference Sold in Europe	Substance > 0.1%
Substance Name	CAS Number
No Substance Content	

Maintenance

Life Cycle

Filters should be stored in their original packaging in a cool, dry, non contaminated atmosphere. Storage under conditions

other than those specified by the manufacturer may affect the shelf life.

Temperature range of storage conditions: -10°C/+40°C

Maximum humidity of storage conditions: 90% RH

Care Instructions

Conditions of use (temperature range, maximum humidity, etc.) :

Temperature range : -10°C/+40°C

Maximum humidity : 90% RH

Restrictions of use :

In an explosive atmosphere.

- If the concentration of oxygen is less than 19.5% by volume or in an oxygen enriched environment.
- If the package unsealed or damaged.

Packaging

EAN Code

3603830343063

Unit of Measure

EA

Quantity per Box/Pack/Case

5

Quantity per Carton

25

Country of Origin

United States