Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

sources	LLLOAILD KLOOI	ATION (LO) 2019/2	1015 with regard to energ	gy labelling of light	
Supplier's name	e or trade mark:	LEDVANCE			
Supplier's address: LEDVANCE GmbH, Parkring 29-33, 85748 Garching, DE					
Model identifie	er: AC41908				
Type of light so	urce:				
Lighting techno	logy used:	LED	Non-directional or directional:	NDLS	
Light source cap-type		E27			
(or other electric interface)					
Mains or non-m	nains:	MLS	Connected light source (CLS):	No	
Colour-tuneable light source:		No	Envelope:	-	
High luminance light source:		No			
Anti-glare shield:		No	Dimmable:	Yes	
		Product para	T	T -	
Parameter		Value	Parameter	Value	
		General product p			
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		8	Energy efficiency class	G	
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		360 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	1 800	
On-mode power (P _{on}), expressed in W		7,8	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80	
Outer dimen-	Height	140	Spectral power dis-	See image	
sions without separate con- trol gear, light- ing control	Width Depth	64 64	tribution in the range 250 nm to 800 nm, at full-load	in last page	

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	30			
		Chromaticity coordinates (x and y)	0,502 0,415			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	0	Survival factor	0,90			
the lumen maintenance factor	0,93					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		If yes then replace- ment claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4			

(a)'-': not applicable; (b)'-': not applicable;

